



INHOUSE RAPID PROTOTYPING OF ELECTRONICS

Breakthrough solution for traditional development challenges
One-stop shop for design and manufacturing



RESHAPE
PERFORMANCE



RESHAPE
DEVELOPMENT
CYCLES



RESHAPE
FORM FACTOR

NANODIMENSION

PRINTER CAPABILITIES PRINTER

Build Volume	160 mm x 160 mm x 1,700 mm
Inks	Optimized silver nano particles and dielectric inks
Supported File Formats	All major eCAD and mCAD software, ODB++, Gerber & Excellon, STL, OBJ
Resolution	18 µm (x), 18 µm (y), 10 µm (z)
Min. Line / Space	100 µm traces / 150 µm spacing
Min. BGA Pitch	400 µm
Min. Via	200 µm
Min. Dielectric Layer Thickness	5.4 µm
Min. Conductive Layer Thickness	1.3 µm
Conductivity (Relative to Copper)	100 µm – 125 µm traces width: 29% ± 4% Trace width ≥ 150 µm: 33% ± 4%
Dielectric Constant (Dk) @ 2 GHz / 15 GHz	2.98 / 2.92
Tangential Loss (Df) @ 2 GHz / 15 GHz	0.02 / 0.02

PRINTER SPECIFICATIONS

Dimensions	1,400 mm x 800 mm x 1,800 mm
Weight	520 kg, (1,150lbs)
Power Supply*	230 VAC, 20 A, 50-60 Hz
Network Connectivity	Ethernet TCP / IP 10/ 100 /1000
Operational Humidity	Above 35% non-condensing
Operational Temperature	18°C (64°F) to 25°C (77°F)
Regulatory Compliance	UL, CE, FCC
Deposition Technology	Piezo drop-on-demand inkjet
Number of Printheads	2, one for each ink: conductive and dielectric
Software	FLIGHT HUB Software Suite

*Must use UPS (Uninterruptible Power Supply)



DragonFly^{IV+}

www.nano-di.com

www.nano-di.comsales@nano-di.com

2025 © Nano Dimension Ltd.

All rights reserved.